

Fiche de données de sécurité selon 1907/2006/CE, Article 31

Date d'impression : 05.11.2019

Révision: 05.11.2019

RUBRIQUE 1: Identification de la substance/du mélange et de la société/l'entreprise

1.1 Identificateur de produit

| | |
|---------------------------|-----------------------|
| · Nom du produit: | ACETONE |
| · Code du produit: | 0008 |
| · No CAS: | 67-64-1 |
| · Numéro CE: | 200-662-2 |
| · Numéro index: | 606-001-00-8 |
| · Numéro d'enregistrement | 01-2119471330-49-XXXX |

1.2 Utilisations identifiées pertinentes de la substance ou du mélange et utilisations déconseillées

· Emploi de la substance / de la préparation Voir annexe 1
Solvants
Fabrication de produits chimiques

1.3 Renseignements concernant le fournisseur de la fiche de données de sécurité

| | | |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| · Producteur/fournisseur: | Société CHARBONNEAUX BRABANT Société P. BRABANT Société FLOURENT BRABANT Société BRABANT CHIMIE Société HAUGUEL Saint Ouen Société HAUGUEL Gonfreville | TEL: 03-26-49-58-70 TEL: 03-20-41-28-05 TEL: 03-20-41-28-05 TEL: 02-38-87-81-75 TEL: 01-30-37-00-04 TEL: 02-32-79-55-00 |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|

· Service chargé des renseignements: Service Sécurité de la société CHARBONNEAUX BRABANT
52 rue de Justice - Z.I. Port Sec
51100 REIMS
Tel: 03 26 49 58 70
Courriel: chimie@charbonneaux.com

· **1.4 Numéro d'appel d'urgence:** ORFILA téléphone: 01 45 42 59 59
SAMU : 15
POMPIERS: 18
Emergency Number 112
Pour connaître la liste des médecins de garde contactez le 15.

RUBRIQUE 2: Identification des dangers

2.1 Classification de la substance ou du mélange

· Classification selon le règlement (CE) n° 1272/2008



GHS02 flamme

Flam. Liq. 2 H225 Liquide et vapeurs très inflammables.



GHS07

Eye Irrit. 2 H319 Provoque une sévère irritation des yeux.
STOT SE 3 H336 Peut provoquer somnolence ou vertiges.

2.2 Éléments d'étiquetage

· Etiquetage selon le règlement (CE) n° 1272/2008
· Pictogrammes de danger

La substance est classifiée et étiquetée selon le règlement CLP.



GHS02



GHS07

· Mention d'avertissement
· Mentions de danger

Danger
H225 Liquide et vapeurs très inflammables.
H319 Provoque une sévère irritation des yeux.
H336 Peut provoquer somnolence ou vertiges.

· Conseils de prudence

Tenir hors de portée des enfants.
En cas de consultation d'un médecin, garder à disposition le récipient ou l'étiquette.
P210 Tenir à l'écart de la chaleur, des surfaces chaudes, des étincelles, des flammes nues et de toute autre source d'inflammation. Ne pas fumer.
P261 Éviter de respirer les brouillards/vapeurs/aérosols.
P271 Utiliser seulement en plein air ou dans un endroit bien ventilé.
P280 Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage/une protection auditive.
P303+P361+P353 EN CAS DE CONTACT AVEC LA PEAU (ou les cheveux): Enlever immédiatement tous les vêtements contaminés. Rincer la peau à l'eau [ou se doucher].

(suite page 2)

FR

Nom du produit: ACETONE

(suite de la page 1)

P304+P340 EN CAS D'INHALATION: transporter la personne à l'extérieur et la maintenir dans une position où elle peut confortablement respirer.

P305+P351+P338 EN CAS DE CONTACT AVEC LES YEUX: Rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.

P312 Appeler un CENTRE ANTIPOISON/un médecin en cas de malaise.

P403+P235 Stocker dans un endroit bien ventilé. Tenir au frais.

P405 Garder sous clef.

P501 Éliminer le contenu/réceptacle dans un centre de collecte des déchets dangereux conformément à la réglementation locale et nationale.

EUH066 L'exposition répétée peut provoquer dessèchement ou gerçures de la peau.

- Indications complémentaires:
- Indications particulières concernant les dangers pour l'homme et l'environnement:

Le produit ne possède pas, ou n'engendre pas en cours d'utilisation, d'autres propriétés dangereuses qui ne feraient pas l'objet d'une classification selon le règlement (CE) n°1272/2008.

· **2.3 Autres dangers**

- Résultats des évaluations PBT et vPvB

· PBT:

Le produit ne possède pas de propriétés PBT telles que définies à l'annexe XIII du règlement (CE) n°1907/2006.

Non applicable.

· vPvB:

Le produit ne possède pas de propriétés vPvB telles que définies à l'annexe XIII du règlement (CE) n°1907/2006.

Non applicable.

RUBRIQUE 3: Composition/informations sur les composants

· **3.1 Substances**

- No CAS Désignation
- Code(s) d'identification

67-64-1 Diméthylcétone

- Numéro CE:
- Numéro index:
- SVHC

200-662-2

606-001-00-8

néant

RUBRIQUE 4: Premiers secours

· **4.1 Description des premiers secours**

- Remarques générales:

Contacter le personnel secouriste et le service Hygiène Sécurité Environnement.

LA RAPIDITE EST ESSENTIELLE.

- Après inhalation:

En cas d'inconscience, coucher et transporter la personne en position latérale stable.

Amener les sujets à l'air frais et les garder au calme.

- Après contact avec la peau:

Laver immédiatement à l'eau.

En cas d'irritation persistante de la peau, consulter un médecin.

Enlever immédiatement les vêtements contaminés par le produit.

- Après contact avec les yeux:

Rincer les yeux, pendant 15 minutes, sous l'eau courante en écartant bien les paupières et consulter un ophtalmologiste

Vérifier que la victime ne porte pas de verres de contact, les retirer.

- Après ingestion:

Tourner sur le côté une personne couchée sur le dos, qui est en train de vomir.

Ne pas faire vomir sauf indication contraire du corps médical

· **4.2 Principaux symptômes et effets, aigus et différés**

Etourdissement

· **4.3 Indication des éventuels soins médicaux immédiats et traitements particuliers nécessaires**

Pas de traitement spécifique requis.

RUBRIQUE 5: Mesures de lutte contre l'incendie

· **5.1 Moyens d'extinction**

- Moyens d'extinction:

CO2, poudre d'extinction ou eau pulvérisée. Combattre les foyers importants avec de l'eau pulvérisée ou de la mousse résistant à l'alcool.

Adapter les mesures d'extinction d'incendie à l'environnement.

- Produits extincteurs déconseillés pour des raisons de sécurité:

Un jet d'eau à grand débit peut propager le feu

· **5.2 Dangers particuliers résultant de la substance ou du mélange**

Monoxyde de carbone (CO)

Dioxyde de carbone

Des vapeurs peuvent former avec l'air un mélange explosif.

Les eaux de ruissellement vers les égouts peut provoquer un incendie ou une explosion.

· **5.3 Conseils aux pompiers**

- **Équipement spécial de sécurité:**

Porter un appareil de respiration indépendant de l'air ambiant.

Ne pas inhaler les gaz d'explosion et les gaz d'incendie.

- Autres indications

Refroidir les récipients en danger en pulvérisant de l'eau.

FR

(suite page 3)

Nom du produit: ACETONE

(suite de la page 2)

RUBRIQUE 6: Mesures à prendre en cas de dispersion accidentelle

- **6.1 Précautions individuelles, équipement de protection et procédures d'urgence**
Porter un équipement de sécurité. Eloigner les personnes non protégées.
Eviter le contact avec la peau et les yeux
NE PAS TOUCHER ni marcher dans le produit répandu.
- **6.2 Précautions pour la protection de l'environnement:**
Eviter de rejeter à l'égout, les fosses et les caves.
En cas de pénétration dans les eaux ou les égouts, avertir les autorités compétentes.
Ne pas rejeter dans les canalisations, dans les eaux de surface et dans les nappes d'eau souterraines.
- **6.3 Méthodes et matériel de confinement et de nettoyage:**
Recueillir les liquides à l'aide d'un produit absorbant (sable, kieselguhr, neutralisant, liant universel, sciure).
Assurer une aération suffisante.
Utiliser du matériel antidéflagrant
Le nettoyage à grandes eaux de quantité importantes en direction des égouts n'est pas autorisé.
- **6.4 Référence à d'autres rubriques**
Afin d'obtenir des informations pour une manipulation sûre, consulter le chapitre 7.
Afin d'obtenir des informations sur les équipements de protection personnels, consulter le chapitre 8.
Afin d'obtenir des informations sur l'élimination, consulter le chapitre 13.

RUBRIQUE 7: Manipulation et stockage

- **7.1 Précautions à prendre pour une manipulation sans danger**
Veiller à une bonne ventilation/aspiration du poste de travail.
Eviter la formation d'aérosols.
Convoyage pneumatique uniquement avec de l'azote.
Porter les équipements de protection requis avant toute manipulation (voir chapitre 8)
Si possible, utiliser un système de transfert clos.
Reporter l'étiquetage d'origine sur tout récipient utilisé pour un prélèvement.
Prévoir des douches et fontaines oculaires sur les lieux d'utilisation.
- Préventions des incendies et des explosions:
Tenir à l'abri des sources d'inflammation - ne pas fumer.
Utiliser des appareils et armatures antidéflagrantes ainsi que des outils ne produisant pas d'étincelle.
Des vapeurs peuvent former avec l'air un mélange explosif.
Les équipements appropriés pour faire face aux incendies, les déversements et les fuites doivent être facilement accessibles.
Mise à la terre des équipements
- **7.2 Conditions d'un stockage sûr, y compris d'éventuelles incompatibilités**
- Stockage:
Exigences concernant les lieux et conteneurs de stockage:
Prévoir des sols étanches et résistant aux solvants.
Ne conserver que dans l'emballage d'origine.
N'utiliser que des emballages spécialement agréés pour la matière/le produit.
Les réservoirs de stockage doivent avoir une liaison équipotentielle électrique et une mise à la terre.
Selon les exigences particulières relatives au lieu de stockage, prévoir un système de rétention.
- Indications concernant le stockage commun:
Ne pas stocker avec les aliments.
Conserver à l'écart des Produits incompatibles.
Ne pas stocker avec des substances oxydantes ou acides.
- Autres indications sur les conditions de stockage:
Stocker au frais et au sec dans des emballages bien fermés.
Protéger de la forte chaleur et du rayonnement direct du soleil.
- **7.3 Utilisation(s) finale(s) particulière(s)**
Pas d'autres informations importantes disponibles.

RUBRIQUE 8: Contrôles de l'exposition/protection individuelle

- Indications complémentaires pour l'agencement des installations techniques: Sans autre indication, voir point 7.

· **8.1 Paramètres de contrôle**

- Composants présentant des valeurs-seuil à surveiller par poste de travail:

CAS: 67-64-1 Diméthylcétone

| | |
|-----------------|---------------------------------------------------------------------------------------------------------------|
| VME (France) | Valeur momentanée: 2420 mg/m ³ , 1000 ppm Valeur à long terme: 1210 mg/m ³ , 500 ppm |
| PEL (U.S.A.) | Valeur à long terme: 2400 mg/m ³ , 1000 ppm |
| REL (U.S.A.) | Valeur à long terme: 590 mg/m ³ , 250 ppm |
| TLV (U.S.A.) | Valeur momentanée: 1187 mg/m ³ , 500 ppm Valeur à long terme: 594 mg/m ³ , 250 ppm |
| AGW (Allemagne) | BEI Valeur à long terme: 1200 mg/m ³ , 500 ppm 2(I);AGS, DFG, EU, Y |

(suite page 4)

FR

Nom du produit: ACETONE

(suite de la page 3)

· DNEL

DNEL (OTH)
Utilisation Finale: Travailleurs
Voies d'exposition: Inhalation
Effets potentiels sur la santé: Effets aigus, Effets locaux
Durée exposition: 1h
Valeur: 2420 mg/m3 - 1000ppm

Utilisation finale: Travailleurs
Voies d'exposition: Contact avec la peau
Effets potentiels sur la santé: Effets chroniques
Durée d'exposition: 8h
Valeur: 186 mg/kg

Utilisation finale: Travailleurs
Voies d'exposition: Inhalation
Effets potentiels sur la santé: Effets chroniques
Valeur 1210 mg/m3 - 500ppm

Utilisation finale: Consommateurs
Voies d'exposition: Contact avec la peau
Effets potentiels sur la santé: Effets chroniques
Durée exposition: 24h
Valeur: 62 mg/kg

Utilisation finale: Consommateurs
Voies d'exposition: Inhalation
Effets potentiels sur la santé: Effets chroniques
Durée exposition: 24h
Valeur: 200 mg/m3

Utilisation finale: Consommateurs
Voies d'exposition: Ingestion
Effets potentiels sur la santé: Effets chroniques
Valeur: 62 mg/kg

· PNEC

PNEC (OTH)
Eau douce: 10.6mg/l
Eau de mer: 1.06 mg/l
Sédiment d'eau douce: 30.4 mg/kg
Sédiment marin: 3.04 mg/kg
Sol: 29.5 mg/kg

· Composants présentant des valeurs limites biologiques:

CAS: 67-64-1 Diméthylcétone

| | |
|------------------------|-----------------------------------------------------------------------------------------------------------------------|
| BEI (U.S.A.) | 50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific) |
| BGW (Allemagne) | 80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton |

· Remarques supplémentaires:

Le présent document s'appuie sur les listes en vigueur au moment de son élaboration.

· **8.2 Contrôles de l'exposition**

Les mesures de contrôle appropriées pour un lieu de travail particulier dépendent de la façon dont le produit est utilisé et du potentiel d'exposition.
Si les contrôles techniques et les modes opératoires ne sont pas efficaces dans la prévention ou le contrôle de l'exposition, les équipements de protections individuels, qui donnent des résultats satisfaisants, doivent être utilisés.

· Equipement de protection individuel:

· Mesures générales de protection et d'hygiène:

Respecter les mesures de sécurité usuelles pour l'utilisation de produits chimiques.
Tenir à l'écart des produits alimentaires, des boissons et de la nourriture pour animaux.
Retirer immédiatement les vêtements souillés ou humectés.
Se laver les mains avant les pauses et en fin de travail.
Ne pas inhaler les gaz, les vapeurs et les aérosols.
Eviter tout contact avec les yeux et avec la peau.
Favoriser la mise en place de mesures de protection collectives par rapport aux mesures de protection individuelle.

· Protection respiratoire:

Utiliser un appareil de protection respiratoire si la ventilation est insuffisante.
En cas de risque d'exposition au delà des valeurs moyennes d'exposition, port obligatoire d'un équipement individuel de protection respiratoire.
Utiliser des appareils conformes à une norme approuvée.

· Filtre recommandé pour une utilisation momentanée:

Attention! Les filtres ont une durée d'utilisation limitée.
Filtre combiné adéquat par exemple ABEK- P2

· Protection des mains:



Gants de protection

Norme EN 374
Changer régulièrement les gants.
Contrôler la perméabilité avant chaque nouvelle utilisation du gant.
Choix du matériau des gants en fonction des temps de pénétration, du taux de perméabilité et de la dégradation. Il convient de tenir compte du fait que la résistance d'un gant est influencée par des facteurs tels que la température

(suite page 5)

Fiche de données de sécurité

selon 1907/2006/CE, Article 31

Date d'impression : 05.11.2019

Révision: 05.11.2019

Nom du produit: ACETONE

· Matériau des gants

Gants laminés multicouches.

Gants en néoprène

Le choix de gants appropriés ne dépend pas seulement du matériau, mais également d'autres critères de qualité qui peuvent varier d'un fabricant à l'autre.

Épaisseur du matériau recommandée: $\geq 0,5$

· Temps de pénétration du matériau des gants

Le temps de pénétration exact est à déterminer par le fabricant des gants de protection et à respecter. Il faut noter que la durabilité des gants de protection chimique peut être notablement plus courte que le temps de pénétration mesuré par la norme EN374 en raison des nombreux effets extérieurs spécifiques à un poste de travail.

Valeur pour la perméabilité: taux ≥ 240 min

· Protection des yeux:



Lunettes de protection hermétiques

· Protection du corps:

Vêtements de travail protecteurs

(suite de la page 4)
d'utilisation du produit, sa concentration, l'épaisseur du gant, le temps d'immersion. Préserver du risque chimique demande de connaître également l'ensemble des autres paramètres propres au poste de travail (risque mécanique, thermique, dextérité requise, manipulation de pièces abrasives).

Se référer aux informations sur les résistances chimiques du fabricant de chaque gant et mener un essai préalable pour déterminer si le gant est adapté aux conditions d'utilisations réelles.

RUBRIQUE 9: Propriétés physiques et chimiques

· 9.1 Informations sur les propriétés physiques et chimiques essentielles

· Indications générales.

· Aspect:

Forme:

Liquide

Couleur:

Incolore

· Odeur:

Caractéristique

· Seuil olfactif:

Information non disponible

Non déterminé.

· valeur du pH:

Non déterminé.

· Changement d'état

Point de fusion/point de congélation: -94,7 °C

Point initial d'ébullition et intervalle d'ébullition: 55,8-56,6 °C

· Point d'éclair:

-17 °C

· Inflammabilité (solide, gaz):

Non applicable.

· Température d'auto-inflammation:

465 °C

· Température de décomposition:

Non déterminé.

· Température d'auto-inflammabilité:

Non déterminé.

· Propriétés explosives:

Le produit n'est pas explosif; toutefois, des mélanges explosifs vapeur-air peuvent se former.

· Limites d'explosion:

Inférieure:

2,5 Vol %

Supérieure:

13 Vol %

· Pression de vapeur à 20 °C:

240 hPa

· Densité à 20 °C:

0,79 g/cm³

· Solubilité dans/miscibilité avec l'eau:

Entièrement miscible

· Coefficient de partage: n-octanol/eau:

Voir chapitre 12

Non déterminé.

· Viscosité:

Dynamique à 20 °C:

0,32 mPas

Cinématique:

Non déterminé.

· 9.2 Autres informations

Pas d'autres informations importantes disponibles.

RUBRIQUE 10: Stabilité et réactivité

· 10.1 Réactivité

Pas d'autres informations importantes disponibles.

· 10.2 Stabilité chimique

· Décomposition thermique/conditions à éviter:

Pas de décomposition en cas d'usage conforme.

· 10.3 Possibilité de réactions dangereuses

Aucune réaction dangereuse connue.

· 10.4 Conditions à éviter

Chaleur / source de chaleur

Éviter l'accumulation de charges électrostatiques.

· 10.5 Matières incompatibles:

Les bases fortes

Peroxydes (H₂O₂, Na₂O₂, K₂O)

Acides oxydants et sels (HNO₃, MnO₄K.)

Oxydes métalliques (CrO₃, HgO)

Halogènes: fluor, chlore, brome, iode

(suite page 6)

FR

Fiche de données de sécurité

selon 1907/2006/CE, Article 31

Date d'impression : 05.11.2019

Révision: 05.11.2019

Nom du produit: ACETONE

(suite de la page 5)

- **10.6 Produits de décomposition dangereux:** Monoxyde de carbone
La combustion génère des oxydes de carbone

RUBRIQUE 11: Informations toxicologiques

· 11.1 Informations sur les effets toxicologiques

- **Toxicité aiguë:** Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

- Valeurs LD/LC50 déterminantes pour la classification:

| | | |
|----------|----------|--------------------|
| Oral | LD50 | 5.800 mg/kg (rat) |
| Dermique | LD50 | 20.000 mg/kg (rbt) |
| | NOEC 48h | 3.400 MG/LITRE (5) |

- Par voie orale: Les données disponibles indiquent que les critères de classification ne sont pas remplis
- Par voie cutanée: Les données disponibles indiquent que les critères de classification ne sont pas remplis
- Par inhalation: Les données disponibles indiquent que les critères de classification ne sont pas remplis
- **Effet primaire d'irritation:**
 - Corrosion cutanée/irritation cutanée: Compte tenu des données disponibles, les critères de classification ne sont pas remplis. Provoque une sévère irritation des yeux.
 - Lésions oculaires graves/irritation oculaire: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
- **Sensibilisation:** Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
- **Effets CMR (cancérogène, mutagène et toxique pour la reproduction):**
 - Mutagénicité sur les cellules germinales: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
 - Cancérogénicité: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
 - Toxicité pour la reproduction: Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
 - **Toxicité spécifique pour certains organes cibles - exposition unique:** Peut provoquer somnolence ou vertiges.
 - **Toxicité spécifique pour certains organes cibles - exposition répétée:** Compte tenu des données disponibles, les critères de classification ne sont pas remplis.
 - **Danger par aspiration:** Compte tenu des données disponibles, les critères de classification ne sont pas remplis.

RUBRIQUE 12: Informations écologiques

· 12.1 Toxicité

- Toxicité aquatique:

| | |
|-------------------|-------------------------------------------------------------------------------------------------------|
| CE50 (écologique) | >100 mg/l (ALGUES) (Pseudokirchneriella subcapitata, Essai en statique) (valeur de la littérature) |
| | >100 mg/l (DAPHNIES) (Daphnia magna, Essai en statique) (valeur de la littérature) |
| LC50 (écologique) | >100 mg/l (POISSONS) (Salmo gairdneri, essai en statique) (valeur de la littérature) |

- **12.2 Persistance et dégradabilité:** Facilement biodégradable.
- **12.3 Potentiel de bioaccumulation:** Le produit s'évapore rapidement s'il est déversé sur le sol
- **12.4 Mobilité dans le sol:** Pas d'autres informations importantes disponibles.
- Autres indications écologiques:
 - Valeur DCO: 1920 MG/G
 - Valeur DBO5: 1850 MG/G
 - Indications générales: Ne pas laisser pénétrer dans la nappe phréatique, les eaux ou les canalisations.
- **12.5 Résultats des évaluations PBT et VPVB:**
 - PBT: Le produit ne possède pas de propriétés PBT telles que définies à l'annexe XIII du règlement (CE) n°1907/2006. Non applicable.
 - vPvB: Le produit ne possède pas de propriétés vPvB telles que définies à l'annexe XIII du règlement (CE) n°1907/2006. Non applicable.
- **12.6 Autres effets néfastes:** Pas d'autres informations importantes disponibles.

RUBRIQUE 13: Considérations relatives à l'élimination

· 13.1 Méthodes de traitement des déchets

- **Recommandation:** Ne doit pas être évacué avec les ordures ménagères. Ne pas laisser pénétrer dans les égouts. Doit faire l'objet d'un traitement spécial conformément aux prescriptions légales. Pour la manipulation des déchets, prendre les précautions définies aux chapitres 7 et 8. Réutilisation ou recyclage lorsque c'est possible, sinon incinération selon les méthodes recommandées d'élimination.
- **Code déchet:** Des données concernant l'utilisation par le consommateur sont nécessaires pour déterminer le code déchet.
- **Emballages non nettoyés:** Les emballages ne pouvant pas être nettoyés doivent être évacués de la même manière que le produit. Ne pas découper, perforez ou souder sur ou à proximité des emballages vides. Les emballages vides peuvent contenir des résidus dangereux. Ne pas retirer l'étiquette de l'emballage tant qu'il n'est pas nettoyé. Ne pas traiter l'emballage vide comme un déchet ménager. Ne pas incinérer un emballage fermé.
- **Recommandation:**

(suite page 7)

FR

Nom du produit: ACETONE

· Produit de nettoyage recommandé: Eau, éventuellement avec des produits de nettoyage

(suite de la page 6)

RUBRIQUE 14: Informations relatives au transport

· **14.1 Numéro ONU**

· ADR, IMDG, IATA UN1090

· **14.2 Désignation officielle de transport de l'ONU**

· ADR 1090 ACÉTONE
· IMDG, IATA ACETONE

· **14.3 Classe(s) de danger pour le transport**

· ADR



· Classe 3 (F1) Liquides inflammables.
· Étiquette 3

· IMDG, IATA



· Class 3 Liquides inflammables.
· Label 3

· **14.4 Groupe d'emballage**

· ADR, IMDG, IATA II

· **14.5 Dangers pour l'environnement:**

Non applicable.

· **14.6 Précautions particulières à prendre par l'utilisateur**

· Attention: Liquides inflammables.
· Indice Kemler: 33
· No EMS: F-E,S-D

· **14.7 Transport en vrac conformément à l'annexe II de la convention Marpol et au recueil IBC**

Non applicable.

· Indications complémentaires de transport:

· ADR

· Quantités limitées (LQ) 1L
· Quantités exceptées (EQ) Code: E2
Quantité maximale nette par emballage intérieur: 30 ml
Quantité maximale nette par emballage extérieur: 500 ml

· Catégorie de transport 2

· Code de restriction en tunnels D/E

· IMDG

· Limited quantities (LQ) 1L
· Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· "Règlement type" de l'ONU: UN 1090 ACÉTONE, 3, II

RUBRIQUE 15: Informations relatives à la réglementation

· **15.1 Réglementations/législation particulières à la substance ou au mélange en matière de sécurité, de santé et d'environnement**

· TSCA (Loi sur le contrôle des substances

· Principales Inventory of Chemicals and Chemical Substances la substance est comprise

· Chinese Chemical Inventory of Existing Chemical Substances la substance est comprise

· Australian Inventory of Chemical Substances la substance est comprise

· Canadian Domestic Substances List (DSL) la substance est comprise

· Korean Existing Chemical Inventory la substance est comprise

· Etiquetage selon le règlement (CE) n° 1272/2008 voir chapitre 2

· Directive 2012/18/UE

· Substances dangereuses désignées - ANNEXE I la substance n'est pas comprise

· Catégorie SEVESO P5c LIQUIDES INFLAMMABLES

(suite page 8)

FR

Fiche de données de sécurité

selon 1907/2006/CE, Article 31

Date d'impression : 05.11.2019

Révision: 05.11.2019

Nom du produit: ACETONE

(suite de la page 7)

- Quantité seuil (tonnes) pour l'application des exigences relatives au seuil bas 5.000 t
- Quantité seuil (tonnes) pour l'application des exigences relatives au seuil haut 50.000 t
- RÉGLEMENT (CE) N° 1907/2006 ANNEXE XVII Conditions de limitation: 3, 40
- Indications sur les restrictions de travail: Rubriques nomenclature ICPE (France): 4330, 4331
Respecter les réglementations nationales applicables (ICPE, Code du travail, Maladies professionnelles)
- Substances extrêmement préoccupantes (SVHC) selon REACH, article 57 Néant
- **15.2 Évaluation de la sécurité chimique:** Une évaluation de la sécurité chimique a été réalisée.

RUBRIQUE 16: Autres informations

Ces informations ne dispensent pas l'utilisateur de contrôler le produit et n'engagent en aucun cas notre responsabilité quant à l'utilisation pour laquelle il le destine.

Ces indications sont fondées sur l'état actuel de nos connaissances, mais ne constituent pas une garantie quant aux propriétés du produit et ne donnent pas lieu à un rapport juridique contractuel.

- Domaines d'application selon la directive 98/8/CE - Règlement CE 528/2012. Non concerné
- Service établissant la fiche technique: -
voir Rubrique 1
- Contact: -
Voir Rubrique 1
- Acronymes et abréviations:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - SVHC: Substances of Very High Concern
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Liquides inflammables – Catégorie 2
 - Eye Irrit. 2: Lésions oculaires graves/irritation oculaire – Catégorie 2
 - STOT SE 3: Toxicité spécifique pour certains organes cibles (exposition unique) – Catégorie 3
- * Données modifiées par rapport à la version précédente

FR

(suite page 9)

Fiche de données de sécurité
selon 1907/2006/CE, Article 31

Date d'impression : 05.11.2019

Révision: 05.11.2019

Nom du produit: ACETONE

(suite de la page 8)

Annexe: Scénario d'exposition

· **Désignation brève du scénario d'exposition** Voir annexe 1.

FR

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Industrial

2010-08-23

Identified Industrial Generic Exposure Scenarios (GESs) of Acetone

| GES No. EC No. CAS No. | Subsector | Main SU | Description | PROC | ERC | Acetone 200-662-2 67-64-1 |
|------------------------------|---------------------------------------------------------------------|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|----------------------------------------------------------------------|
| 1 | Manufacture, Processing and Distribution of substances and mixtures | All Industrial Uses (SU3) | Manufacture, Processing (see examples below1), Formulation and Distribution of the substance or mixtures. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities | PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC14, PROC15 | ERC1, ERC2, ERC4, ERC6a ERCs are to be checked with the ECT tool | x |
| 2 | Use in laboratories | All Industrial Uses (SU3) | Use of the substance within laboratory settings, including material transfers and equipment cleaning | PROC10, PROC15 | ERC4 ERCs are to be checked with the ECT tool | x + PROC19 |
| 3 | Uses in Coatings | All Industrial Uses (SU3) | Covers the use in coatings (paints, inks, adhesives, and production of textiles, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities. | PROC5, PROC8a, PROC10, PROC13 | ERC4 ERCs are to be checked with the ECT tool | x + PROC1, PROC2, PROC3, PROC4, PROC7, PROC8b, PROC9, PROC15, PROC19 |
| 4 | Use as binders and release agents | All Industrial Uses (SU3) | Covers the use as binders and release agents including material transfers, mixing, application (including spraying and brushing), mould forming and casting, and handling of waste. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13 | ERC5 ERCs are to be checked with the ECT tool | x |
| 5 | Rubber production and processing | All Industrial Uses (SU3) | Manufacture of tyres and general rubber articles, including processing of raw (uncured) rubber, handling and mixing of rubber additives, vulcanising, cooling and finishing. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14 | ERC6d ERCs are to be checked with the ECT tool | x |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Industrial

2010-08-23

| GES No. EC No. CAS No. | Subsector | Main SU | Description | PROC | ERC | Acetone 200-662-2 67-64-1 |
|------------------------------|-----------------------------------------------------|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|------------------------------------------------------------|---------------------------------|
| 6 | Polymer manufacturing | All Industrial Uses (SU3) | Manufacturing of formulated polymers including material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15 | ERC6d ERCs are to be checked with the ECT tool | x |
| 7 | Polymer processing | All Industrial Uses (SU3) | Processing of formulated polymers including material transfers, additives handling (e.g. pigments, stabilisers, fillers, plasticisers, etc.), moulding, curing and forming activities, material re-works, storage and associated maintenance. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC14, PROC15 | ERC6d ERCs are to be checked with the ECT tool | x |
| 9 | Use in Cleaning Agents | All Industrial Uses (SU3) | Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. Exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC19 | ERC4 ERCs are to be checked with the ECT tool | x |
| 10 | Use in Oil field drilling and production operations | All Industrial Uses (SU3) | Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. | PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b | ERC 4 ERCs are to be checked with the ECT tool | x |
| 11 | Blowing agents | All Industrial Uses (SU3) | Use as a blowing agent for rigid and flexible foams, including material transfers, mixing and injection, curing, cutting, storage and packing | PROC1, PROC2, PROC3, PROC8b, PROC9, PROC12 | ERC4, (ERC10a) ERCs are to be checked with the ECT tool | x |
| 12 | Mining chemicals | All Industrial Uses (SU3) | Covers the use of the substance in extraction processes at mining operations, including material transfers, winning and separation activities, and substance recovery and disposal. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC8b, PROC9 | ERC8d ERCs are to be checked with the ECT tool | x |

¹ Examples for processing: use as intermediate, use as monomer etc. use as solvent, use for the manufacturing of resins

² Polymer Examples: FRP, UV, VE

Please note also: PC's and AC's are only for consumer.
For checking ERC's please use the respective environmental calculation tool (ECT) ECT Acetone or ECT Phenol or ECT Cumene or ECT AMS or ECT ACP

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Industrial

2010-08-23

Identified Industrial PROCs

| PROC No. | Acetone |
|--------------------|-----------|
| EC No. | 200-662-2 |
| CAS No. | 67-64-1 |
| PROC1 | x |
| PROC2 | x |
| PROC3 | x |
| PROC4 | x |
| PROC5 | x |
| PROC6 | x |
| PROC7 | x |
| PROC8a | x |
| PROC8b | x |
| PROC9 | x |
| PROC10 (2 uses) | x |
| PROC12 | x |
| PROC13 | x |
| PROC14 | x |
| PROC15 | x |
| PROC19 | x |
| Sum | 16 |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Industrial Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-ind \ Identification

| Substance specific information | | Reference Values | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------------------------|---------------|
| Substance | 67-64-1 | DNEL worker - inhalation (long term) | 500 ppm |
| CASnr | 233 nPA | DNEL worker - inhalation (short term) | ppm |
| Substance volatility: | high | DNEL worker - dermal (long term) | 186 mg/kg/day |
| TRA volatility range | high | | |
| physical property | liquid | | |
| Section 1 | | | |
| Exposure Scenario Title | | | |
| Main sector of Use: SU3 = All Industrial Uses | | | |
| All Industrial Processes relevant for Acetone and Acetone containing products. | | | |
| Life Cycle Stage / Sector of Use | | | |
| SU3 = All Industrial Uses | | | |
| Applicable Use Descriptors | | | |
| (PROC or PC) | | | |
| PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC12, PROC13, PROC14, PROC15, PROC19 | | | |
| Applicable Use Descriptors | | | |
| ERCs and local conditions are to be checked with the Excel tool ECT Acetone | | | |
| Default Operational Conditions | | | |
| Product characteristics | | | |
| Acute Hazard | | | |
| R phrases: 11-Highly flammable, 36-Irritating to eyes, 56-Repeated exposure may cause skin dryness or cracking, 67-Vapours may cause drowsiness and dizziness | | | |
| General measures | | | |
| Locate bulk storage outdoors [E2] | | | |
| Use suitable eye protection [PPE26] | | | |
| If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes [PPE20] | | | |
| Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. [E1] | | | |
| Covers percentage substance in the product up to 100 % (unless stated differently) [G13]. | | | |
| Liquid, vapour pressure > 10 kPa [OC5]. | | | |
| Covers daily exposures up to 8 hours (unless stated differently) [G2] | | | |
| Assumes a good basic standard of occupational hygiene is implemented [G1]. | | | |
| concentration of substance in product | | | |
| physical form of product | | | |
| frequency and duration of use | | | |
| other Operational Conditions of use | | | |

4/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Industrial Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-ind \ Identification

| | |
|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Section 2 | Operational conditions and risk management measures |
| Section 2.1 | Control of environmental exposure |
| Product characteristics | substance is a unique structure, ketone, readily biodegradable |
| Amounts used | Annual site tonnage (tonnes/year): please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year |
| Frequency and duration of use | Emission Days (days/year): 3600dy |
| Other Operational Conditions of use affecting environmental exposure | Indoor/Outdoor use |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | Common practices vary across sites thus conservative process release estimates used. Typical technical measures are closed systems or scrubbers or charcoal adsorbers. Typical onsite offgas treatment technology provides removal efficiency of 90 % |
| Organisation measures to prevent/limit release from site | Common practices vary across sites thus conservative process release estimates used. Please use the Excel-Tool 'ECT Acetone' to check your local conditions. |
| Conditions and measures related to municipal sewage treatment plant | Please use the Excel-Tool 'ECT Acetone' to check your local conditions. |
| Conditions and measures related to external treatment of waste for disposal | External treatment and disposal of waste should comply with applicable regulations |
| Conditions and measures related to external recovery of waste | External treatment and disposal of waste should comply with applicable regulations |
| Other environmental control measures additional to above | none |
| Section 2.2 | Control of worker exposure |
| | see chapter RMMs |
| Section 3 | Exposure Estimation |
| 3.1. Health | http://www.reachcentre.com/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx |
| | http://cefic.org/templates/hwPublications.asp?HID=750 |
| 3.2. Environment | ECT Acetone |
| Section 4 | Guidance to check compliance with the Exposure Scenario |
| 4.1. Health | Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| 4.2. Environment | Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |

5/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | Industrial Processes relevant for Acetone and Acetone containing products | | Risk Management Measures (RMMs) | |
|----------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|--------------------------------------------------|------------------------------------------------------------------------------|--|---------------------------------|-----------------------------------------------------------------------------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | | | advised under REACH |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Industrial - SU3 | General exposures (closed systems) [CS15]. | (closed systems) [CS107]; Process sampling [CS2]. ; | | | Sample via a closed loop or other system to avoid exposure [E8]; Handle substance within a closed system [E47]. |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Industrial - SU3 | General exposures (closed systems) [CS15]. | Continuous process [CS54]. ; Process sampling [CS2]. | | | Sample via a closed loop or other system to avoid exposure [E8]; Handle substance within a closed system [E47]. |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Industrial - SU3 | General exposures (closed systems) [CS15]. | Batch process [CS55]. Process sampling [CS2]. | | | Sample via a closed loop or other system to avoid exposure [E8]; Handle substance within a closed system [E47]. |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Industrial - SU3 | Process sampling [CS2]. ; (open systems) [CS108] | | | | |
| 5 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Industrial - SU3 | Mixing operations (open systems) [CS30]. | Batch process [CS55]. Process sampling [CS2]. | | | |
| 6 | PROC 6 - Calendaring operations | Industrial - SU3 | Calendaring (including Banburys) [CS64] | | | | |
| 7 | PROC 7 -Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]. | with local exhaust ventilation [CS109] | | | Ensure material transfers are under containment or extract ventilation [E66]. |
| 8 | PROC 7 -Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]. | | | | Ensure operation is undertaken outdoors [E69]. |
| 9 | PROC 7 -Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]. | | | | Wear a respirator conforming to EN140 with Type A filter or better. [PPE22] |
| 10 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Industrial - SU3 | Bulk transfers [CS14]. | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]. | | | |
| 11 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Industrial - SU3 | Bulk transfers [CS14]. | Dedicated facility [CS81]; Transfer from/pouring from containers [CS22]. | | | |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | Industrial Processes relevant for Acetone and Acetone containing products | | Risk Management Measures (RMMs) | |
|----------------------------|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|--|---------------------------------|-----------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & Typical RMMs | | | |
| 12 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Industrial - SU3 | Small package filling [CS7] | Dedicated facility [CS81]; Pouring from small containers [CS9] | | | advised under REACH |
| 13 | PROC 10 - Roller application or brushing | Industrial - SU3 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] | | | |
| 14 | PROC 10 - Roller application or brushing | Industrial - SU3 | Equipment cleaning and maintenance [CS39] | | | | |
| 15 | PROC 12 - Use of blow agents for foam production | Industrial - SU3 | Foaming [CS132] | Production of foam-based objects [CS125] | | | |
| 16 | PROC 13 - Treatment of articles by dipping and pouring | Industrial - SU3 | Dipping, immersion and pouring [CS4] | | | | |
| 17 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation | Industrial - SU3 | Production or preparation of articles by tableting, compression, extrusion or pelletisation [CS100] | | | | |
| 18 | PROC 15 - Use of laboratory reagents in small scale laboratories | Industrial - SU3 | Laboratory activities [CS36] | | | | |
| 19 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Industrial - SU3 | Hand application - fingerpaints, pastels, adhesives [CS72] | | | | Wear suitable gloves tested to EN374 [PPE15]. |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Industrial Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-Ind \ Inhalation Exposure

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | | | Inhalation Exposure | | | | | | | |
|----------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|------------------------------------------------|-----------------------------------------------------------------------------|----------------------------------|-------------------------|----------------------------------------|---------------------------|----------------------|-----------------|------------------------------------|--------------------------------------------------------------|----------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | TRACLEV: exposure - no modifiers | TRACLEV: efficiency (%) | TRACLEV: ventilation effectiveness (%) | TRAC concentration factor | TRAC duration factor | TRAC RSE factor | Extra exposure modifier (optional) | Free fact. comment to clarify additional modifier (optional) | Proposed Exposure - (point - modified) |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Industrial - SU3 | General exposures (closed systems) [CS15] | Operational Conditions (closed systems) [CS107]; Process sampling [CS2]; | 0.01 | | | | | | | | 0.01 |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled atmosphere | Industrial - SU3 | General exposures (closed systems) [CS15] | Continuous process [CS54]; Process sampling [CS2] | 50.00 | | | | | | | | 50 |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Industrial - SU3 | General exposures (closed systems) [CS15] | Batch process [CS55]; Process sampling [CS2] | 100.00 | | | | | | | | 100 |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for separate phases | Industrial - SU3 | Process sampling [CS2]; (open systems) [CS106] | | 100.00 | | | | | | | | 100 |
| 5 | PROC 5 - Mixing or blending in batch (multiple and/or intermittent contact) | Industrial - SU3 | Mixing operations (open systems) [CS30] | Batch process [CS55]; Process sampling [CS2] | 250.00 | | | | | | | | 250 |
| 6 | PROC 6 - Calendaring operations | Industrial - SU3 | Calendaring (including Beryure) [CS64] | | 250.00 | | | | | | | | 250 |
| 7 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25] | with local exhaust ventilation [CS109] | 500.00 | 95.00 | | | | | | | 25 |
| 8 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25] | | 500.00 | | 30.00 | | | | | | 300 |
| 9 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25] | | 500.00 | | | | | half mask | | | 50 |
| 10 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non-dedicated facilities | Industrial - SU3 | Bulk transfers [CS14] | Non-dedicated facility [CS62]; Transfer from/pouring from containers [CS22] | 250.00 | | | | | | | | 250 |
| 11 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Industrial - SU3 | Bulk transfers [CS14] | Dedicated facility [CS61]; Transfer from/pouring from containers [CS22] | 150.00 | | | | | | | | 150 |
| 12 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Industrial - SU3 | Small package filling [CS7] | Dedicated facility [CS61]; Pouring from small containers [CS9] | 200.00 | | | | | | | | 200 |
| 13 | PROC 10 - Roller application or brushing | Industrial - SU3 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] | 250.00 | | | | | | | | 250 |

8/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

CSR-Worker-Aceton-ind \ Dermal Exposure Industrial Processes relevant for Acetone and Acetone containing products

2010-08-23

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | | Dermal Exposure | | | | | | |
|----------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|---------------------------------------------------------------|------------------------------------------------------------------------------|--------------------------------------------------------|------------------------------------------|--------------------------|------------|------------------------------------|-------------------------------------------------------------|-----------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario & typical RMMs (closed systems) [CS15]; | Operational Conditions (closed systems) [CS107]; Process sampling [CS2]; ; | TRM Predicted Dermal exposure (mg/kg/d) - no modifiers | TRM Dermal exposure LEV reduction factor | TRM concentration factor | PPE factor | extra exposure modifier (optional) | Free text - comment to clarify additional modifier (dermal) | Weighted Dermal exposure (mg/kg/d) - modified |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Industrial - SU3 | General exposures (closed systems) [CS15]; | Process sampling [CS2]; ; | 0.34 | | | | | | 0.34 |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Industrial - SU3 | General exposures (closed systems) [CS15]; | Continuous process [CS54]; Process sampling [CS2]; | 1.37 | | | | | | 1.37 |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Industrial - SU3 | General exposures (closed systems) [CS15]; | Batch process [CS56]; Process sampling [CS2]; | 0.34 | | | | | | 0.34 |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure | Industrial - SU3 | Process sampling [CS2]; ; (open systems) [CS109] | | 6.86 | | | | | | 6.86 |
| 5 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Industrial - SU3 | Mixing operations (open systems) [CS30]; | Batch process [CS56]; Process sampling [CS2]; | 13.71 | | | | | | 13.71 |
| 6 | PROC 6 - Calendaring operations | Industrial - SU3 | Calendaring (including Banbury) [CS64] | | 27.43 | | | | | | 27.43 |
| 7 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]; | with local exhaust ventilation [CS109] | 42.86 | 0.05 | | | | | 2.14 |
| 8 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]; | | 42.86 | | | | | | 42.86 |
| 9 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]; | | 42.86 | | | | | | 42.86 |
| 10 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Industrial - SU3 | Bulk transfers [CS14]; | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]; | 13.71 | | | | | | 13.71 |
| 11 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Industrial - SU3 | Bulk transfers [CS14]; | Dedicated facility [CS81]; Transfer from/pouring from containers [CS22]; | 6.86 | | | | | | 6.86 |
| 12 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Industrial - SU3 | Small package filling [CS7] | Dedicated facility [CS81]; Pouring from small containers [CS8]; | 6.86 | | | | | | 6.86 |

10/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Industrial Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-ind \ Dermal Exposure

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | | Dermal Exposure | | | | | | |
|----------------------------|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|------------------------------------------------|-------------------------------------------------------|-------------------------------------------|---------------------------|------------|------------------------------------|-------------------------------------------------------------|---------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario & typical RMMs | Operational Conditions & typical RMMs | TRIA Predicted Dermal exposure (mg/kg) - no modifiers | TRIA Dermal exposure LEV reduction factor | TRIA concentration factor | PPE factor | extra exposure modifier (optional) | Free text - comment to clarify additional modifier (dermal) | Weighted Dermal exposure (mg/kg) - modified |
| 13 | PROC 10 - Roller application or brushing | Industrial - SU3 | Rolling, Brushing [CS51]. | Or: Equipment cleaning and maintenance [CS39]. | 27.43 | | | | | | 27.43 |
| 14 | PROC 10 - Roller application or brushing | Industrial - SU3 | Equipment cleaning and maintenance [CS39]. | | 27.43 | | | | | | 27.43 |
| 15 | PROC 12 - Use of blow agents for foam production | Industrial - SU3 | Foaming [CS132]. | Production of foam-based objects [CS125]. | 0.34 | | | | | | 0.34 |
| 16 | PROC 13 - Treatment of articles by dipping and pouring | Industrial - SU3 | Dipping, immersion and pouring [CS4]. | | 13.71 | | | | | | 13.71 |
| 17 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation | Industrial - SU3 | Production or preparation of articles by labelling, compression, extrusion or pelletisation [CS100]. | | 0.34 | | | | | | 0.34 |
| 18 | PROC 15 - Use of laboratory reagents in small scale laboratories | Industrial - SU3 | Laboratory activities [CS36]. | | 0.34 | | | | | | 0.34 |
| 19 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Industrial - SU3 | Hand application - fingerpaints, pastels, adhesives [CS72]. | | 141.43 | | | gloves | | | 28.29 |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| | | | | | | | | | | | |

11/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Acetone-Ind \ RCR Industrial Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | Risk Characterization | | | |
|----------------------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|-------------------------------------------------|------------------------------------------------------------------------------|------------------|--------------|------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | RCR (Inhalation) | RCR (dermal) | RCR (all routes) |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Industrial - SU3 | General exposures (closed systems) [CS15]; | (closed systems) [CS107]; Process sampling [CS2]; ; | 0.00002 | 0.002 | 0.002 |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Industrial - SU3 | General exposures (closed systems) [CS15]; | Continuous process [CS54]; Process sampling [CS2]; | 0.10 | 0.01 | 0.11 |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Industrial - SU3 | General exposures (closed systems) [CS15]; | Batch process [CS55]; Process sampling [CS2]; | 0.20 | 0.002 | 0.20 |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Industrial - SU3 | Process sampling [CS2]; (open systems) [CS106] | | 0.20 | 0.04 | 0.24 |
| 5 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Industrial - SU3 | Mixing operations (open systems) [CS30]; | Batch process [CS55]; Process sampling [CS2]; | 0.50 | 0.07 | 0.57 |
| 6 | PROC 6 - Calendaring operations | Industrial - SU3 | Calendaring (including Banburys) [CS64] | | 0.50 | 0.15 | 0.65 |
| 7 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]; | with local exhaust ventilation [CS109] | 0.05 | 0.01 | 0.06 |
| 8 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]; | | 0.70 | 0.23 | 0.93 |
| 9 | PROC 7 - Industrial spraying | Industrial - SU3 | Spraying/fogging by machine application [CS25]; | | 0.10 | 0.23 | 0.33 |
| 10 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Industrial - SU3 | Bulk transfers [CS14]; | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]; | 0.50 | 0.07 | 0.57 |
| 11 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Industrial - SU3 | Bulk transfers [CS14]; | Dedicated facility [CS81]; Transfer from/pouring from containers [CS22]; | 0.30 | 0.037 | 0.34 |

12/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Acetone-Ind \ RCR Industrial Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Industrial Processes relevant for Acetone and Acetone containing products | | Risk Characterization | | |
|----------------------------|------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|--------------|------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Industrial Processes relevant for Acetone and Acetone containing products | RCR (Inhalation) | RCR (dermal) | RCR (all routes) |
| 12 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Industrial - SU3 | Contributing Scenario Small package filling [CS7]. Operational Conditions & typical RMMs Dedicated facility [CS81]; Pouring from small containers [CS9]. | 0.40 | 0.04 | 0.44 |
| 13 | PROC 10 - Roller application or brushing | Industrial - SU3 | Rolling, Brushing [CS51]. Or: Equipment cleaning and maintenance [CS39]. | 0.50 | 0.15 | 0.65 |
| 14 | PROC 10 - Roller application or brushing | Industrial - SU3 | Equipment cleaning and maintenance [CS39]. | 0.50 | 0.15 | 0.65 |
| 15 | PROC 12 - Use of blow agents for foam production | Industrial - SU3 | Foaming [CS132]. Production of foam-based objects [CS125]. | 0.20 | 0.00 | 0.20 |
| 16 | PROC 13 - Treatment of articles by dipping and pouring | Industrial - SU3 | Dipping, immersion and pouring [CS4]. | 0.50 | 0.074 | 0.57 |
| 17 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation | Industrial - SU3 | Production or preparation of articles by tableting, compression, extrusion or pelletisation [CS100]. | 0.10 | 0.00 | 0.10 |
| 18 | PROC 15 - Use of laboratory reagents in small scale laboratories | Industrial - SU3 | Laboratory activities [CS36]. | 0.10 | 0.00 | 0.10 |
| 19 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Industrial - SU3 | Hand application - fingerpaints, pastels, adhesives [CS72]. | 0.50 | 0.15 | 0.65 |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

13/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Professional

2010-08-23

Identified Professional Generic Exposure Scenarios (GESs) of Acetone

| GES No. EC No. CAS No. | Subsector | Main SU | Description | PROC | ERC | Acetone 200-662-2 67-64-1 |
|------------------------------|-----------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| 1 | Use in laboratories | All Professional Uses (SU22) | Use of small quantities within laboratory settings, including material transfers and equipment cleaning | PROC10, PROC15 | ERC8a ERCs are to be checked with the ECT tool | x + PROC19 |
| 2 | Uses in Coatings | All Professional Uses (SU22) | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods), and equipment cleaning, maintenance and associated laboratory activities. | PROC5, PROC8a, PROC10, PROC13 | ERC8a, ERC8c, ERC8d, ERC8f ERCs are to be checked with the ECT tool | x + PROC1, PROC2, PROC3, PROC4, PROC8b, PROC9, PROC11, PROC15, PROC19 |
| 3 | Use as binders and release agents | All Professional Uses (SU22) | Covers the use as binders and release agents including material transfers, mixing, application by spraying, brushing, and handling of waste. | PROC1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC10, PROC11 | ERC8a, ERC8b, ERC8c, ERC8d, ERC8e, ERC8f ERCs are to be checked with the ECT tool | x |
| 4 | Polymer manufacturing | All Professional Uses (SU22) | Manufacturing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance. | PROC8a | ERC8a, ERC8d, ERC8c, ERC8f ERCs are to be checked with the ECT tool | x + PROC1 PROC2 PROC8b PROC9 PROC14 |
| 5 | Polymer processing | All Professional Uses (SU22) | Processing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance. | PROC8a | ERC8a, ERC8d, ERC8c, ERC8f ERCs are to be checked with the ECT tool | x + PROC1 PROC2 PROC8b PROC9 PROC14 |
| 7 | Use in Cleaning Agents | All Professional Uses (SU22) | Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping automated and by hand). | PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC19 | ERC8a ERCs are to be checked with the ECT tool | x + ERC8d |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Professional

2010-08-23

| GES No. EC No. CAS No. | Subsector | Main SU | Description | PROC | ERC | Acetone 200-662-2 67-64-1 |
|------------------------------|-----------------------------------------------------|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|---------------------------------|
| 8 | Use in Oil field drilling and production operations | All Professional Uses (SU22) | Covers the use as a component of cleaning products including pouring/unloading from drums or containers | PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b | ERC8d ERCs are to be checked with the ECT tool | x |
| 9 | Agrochemical uses | All Professional Uses (SU22) | Use as an agrochemical excipient for application by manual or machine spraying, smokes and fogging; including equipment clean-downs and disposal. | PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, PROC19 | ERC8a, ERC8d ERCs are to be checked with the ECT tool | x |
| 10 | De-icing and anti-icing applications | All Professional Uses (SU22) | Ice prevention and de-icing of vehicles, aircraft and other equipment by spraying | PROC1, PROC2, PROC8b, PROC11, PROC19 | ERC8d ERCs are to be checked with the ECT tool | x |
| 11 | Explosives manufacture & use | All Professional Uses (SU22) | Covers exposures arising from the manufacture and use of slurry explosives (including materials transfer, mixing and charging) and equipment cleaning | PROC1, PROC3, PROC5, PROC8a, PROC8b | ERC8d ERCs are to be checked with the ECT tool | x |

² Polymer Examples: FRP, UV, VE

Please note also: PC's and AC's are only for consumer.
For checking ERC's please use the respective environmental calculation tool (ECT) ECT Acetone or ECT Phenol or ECT Cumene or ECT AMS or ECT ACP

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Professional

2010-08-23

Identified Professional PROCs

| PROC No. | Acetone |
|--------------------|-----------|
| EC No. | 200-662-2 |
| CAS No. | 67-64-1 |
| PROC1 | x |
| PROC2 | x |
| PROC3 | x |
| PROC4 | x |
| PROC5 | x |
| PROC6 | x |
| PROC8a | x |
| PROC8b | x |
| PROC9 | x |
| PROC10 (2 uses) | x |
| PROC11 | x |
| PROC13 | x |
| PROC14 | x |
| PROC15 | x |
| PROC19 | x |
| Sum | 15 |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main sector of Use: SU22 = All Professional Uses

CSR-Worker-Acetone-prof \ Identification

| Substance specific information | | Reference Values | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|---------------------------------------|---------------|
| Substance | 67-64-1 | DNEL worker - inhalation (long term) | 500 ppm |
| CASnr | 233 nPA | DNEL worker - inhalation (short term) | ppm |
| Substance volatility: | high | DNEL worker - dermal (long term) | 186 mg/kg/day |
| TRA volatility range | high | | |
| physical property | liquid | | |
| Section 1 | | | |
| Exposure Scenario Title | | | |
| Main sector of Use: SU22 = All Professional Uses | | | |
| All Professional Processes relevant for Acetone and Acetone containing products. | | | |
| Life Cycle Stage / Sector of Use | | | |
| SU22 = All Professional Uses | | | |
| Applicable Use Descriptors (PROC or PC) | | | |
| PROCT1, PROC2, PROC3, PROC4, PROC5, PROC6, PROC8, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC15, PROC19 | | | |
| Applicable Use Descriptors (ERC or SpERC) | | | |
| ERCs and local conditions are to be checked with the Excel tool ECT Acetone | | | |
| Default Operational Conditions | | | |
| Acute Hazard | | | |
| R phrases: 11-Highly flammable, 36-Irritating to eyes, 56-Repeated exposure may cause skin dryness or cracking, 67-Vapours may cause drowsiness and dizziness | | | |
| General measures | | | |
| Locate bulk storage outdoors [E2] | | | |
| Use suitable eye protection [PPE26] | | | |
| If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to EN374 and provide employee skin care programmes [PPE20] | | | |
| Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. [E1] | | | |
| Covers percentage substance in the product up to 100 % (unless stated differently) [G13]. | | | |
| Liquid, vapour pressure > 10 kPa [OC5]. | | | |
| Covers daily exposures up to 8 hours (unless stated differently) [G2] | | | |
| Assumes a good basic standard of occupational hygiene is implemented [G1]. : | | | |
| concentration of substance in product | | | |
| physical form of product | | | |
| frequency and duration of use | | | |
| other Operational Conditions of use | | | |

17/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main sector of Use: SU22 = All Professional Uses

CSR-Worker-Acetone-prof \ Identification

| | |
|------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Section 2 | Operational conditions and risk management measures |
| Section 2.1 | Control of environmental exposure |
| Product characteristics | substance is a unique structure, ketone, readily biodegradable |
| Amounts used | Annual site tonnage (tonnes/year): please use the Excel-Tool 'ECT Acetone' to calculate your maximum tonnage/year |
| Frequency and duration of use | Emission Days (days/year): 3600dy |
| Other Operational Conditions of use affecting environmental exposure | Indoor/Outdoor use |
| Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil | Common practices vary across sites thus conservative process release estimates used. Typical technical measures are closed systems or scrubbers or charcoal adsorbers. Typical onsite offgas treatment technology provides removal efficiency of 90 % |
| Organisation measures to prevent/limit release from site | Common practices vary across sites thus conservative process release estimates used. Please use the Excel-Tool 'ECT Acetone' to check your local conditions. |
| Conditions and measures related to municipal sewage treatment plant | Please use the Excel-Tool 'ECT Acetone' to check your local conditions. |
| Conditions and measures related to external treatment of waste for disposal | External treatment and disposal of waste should comply with applicable regulations |
| Conditions and measures related to external recovery of waste | External treatment and disposal of waste should comply with applicable regulations |
| Other environmental control measures additional to above | none |
| Section 2.2 | Control of worker exposure |
| | see chapter RMMs |
| Section 3 | Exposure Estimation |
| 3.1. Health | http://www.reachcentral.eu/EN/consortium-management/consortia-under-reach/phenol-derivatives-reach-consortium.aspx |
| | http://cefic.org/templates/hwPublications.asp?HID=750 |
| 3.2. Environment | ECT Acetone |
| Section 4 | Guidance to check compliance with the Exposure Scenario |
| 4.1. Health | Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |
| 4.2. Environment | Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. |

18/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | Risk Management Measures (RMMs) | |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------------------------------------------------------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario (closed systems) [CS15]; | Operational Conditions & typical RMMs (closed systems) [CS107]; Process sampling [CS2]. ; | | advised under REACh |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Professional - SU22 | General exposures (closed systems) [CS15]; | (closed systems) [CS107]; Process sampling [CS2]. ; | | Sample via a closed loop or other system to avoid exposure [E8]; Handle substance within a closed system [E47]. |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Professional - SU22 | General exposures (closed systems) [CS15]; | Continuous process [CS54]. ; Process sampling [CS2]. | | Sample via a closed loop or other system to avoid exposure [E8]; Handle substance within a closed system [E47]. |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Professional - SU22 | General exposures (closed systems) [CS15]; | Batch process [CS55]. ; Process sampling [CS2]. | | Sample via a closed loop or other system to avoid exposure [E8]; Handle substance within a closed system [E47]. |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Professional - SU22 | Process sampling [CS2]. ; (open systems) [CS108] | | | |
| 5 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]. | Batch process [CS55]. ; Process sampling [CS2]. ; with local exhaust ventilation [CS109] | | Ensure material transfers are under containment or extract ventilation [E66]. |
| 6 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]. | Batch process [CS55]. ; Process sampling [CS2]. | | Ensure operation is undertaken outdoors [E69]. |
| 7 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]. | Batch process [CS55]. ; Process sampling [CS2]. | | Avoid carrying out activities involving exposure for more than 4 hours [28]. |
| 8 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banburys) [CS64]. with local exhaust ventilation [CS109] | | | Ensure operation is undertaken outdoors [E69]. |
| 9 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banburys) [CS64] | | | Ensure operation is undertaken outdoors [E69]. |
| 10 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banburys) [CS64] | | | Avoid carrying out activities involving exposure for more than 4 hours [28]. |
| 11 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Professional - SU22 | Bulk transfers [CS14]. | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]. ; with local exhaust ventilation [CS109] | | Ensure material transfers are under containment or extract ventilation [E66]. |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | Risk Management Measures (RMMs) | |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | advised under REACh | |
| 12 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]; | Ensure operation is undertaken outdoors [E69]. | |
| 13 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]; | Avoid carrying out activities involving exposure for more than 4 hours [28]. | |
| 14 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Dedicated facility [CS81]; Transfer from/pouring from containers [CS22]; | | |
| 15 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Professional - SU22 | Small package filling [CS7] | Dedicated facility [CS81]; Pouring from small containers [CS9]; | | |
| 16 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39]; ; with local exhaust ventilation [CS109] | Ensure material transfers are under containment or extract ventilation [E66]. | |
| 17 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39]; | Limit the substance content in the product to 25% [OC18]. | |
| 18 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39]; | Avoid carrying out activities involving exposure for more than 4 hours [28]. | |
| 19 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | with local exhaust ventilation [CS109] | Ensure material transfers are under containment or extract ventilation [E66]. | |
| 20 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | Limit the substance content in the product to 25% [OC18]. Ensure operation is undertaken outdoors [E69]. Avoid carrying out activities involving exposure for more than 4 hours [28]. | |
| 21 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | Avoid carrying out activities involving exposure for more than 1 hour [27]. | |
| 22 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | Wear a respirator conforming to EN140 with Type A filter or better. [PPE22] | |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | Risk Management Measures (RMMs) |
|----------------------------|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs |
| 23 | PROC 13 - Treatment of articles by dipping and pouring | Professional - SU22 | Dipping, immersion and pouring [CS4]. | advised under REACh |
| 24 | PROC 14 - Production of preparations or articles by labelling, compression, extrusion, pelletisation | Professional - SU22 | Production or preparation of articles by labelling, compression, extrusion or pelletisation [CS100] | with local exhaust ventilation [CS109] |
| 25 | PROC 14 - Production of preparations or articles by labelling, compression, extrusion, pelletisation | Professional - SU22 | Production or preparation of articles by labelling, compression, extrusion or pelletisation [CS100] | Avoid carrying out activities involving exposure for more than 4 hours [28]. |
| 26 | PROC 15 - Use of laboratory reagents in small scale laboratories | Professional - SU22 | Laboratory activities [CS36]. | |
| 27 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerprints, pastels, adhesives [CS72] | Limit the substance content in the product to 25% [OC18]. Wear suitable gloves tested to EN374 [PPE15]. |
| 28 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerprints, pastels, adhesives [CS72] | Avoid carrying out activities involving exposure for more than 1 hour [27]. |

21/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Professional Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-prof \ Inhalation Exposure

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | | Inhalation Exposure | | | | | | | |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|---------------------------------|------------------------|----------------------------------------|---------------------------|----------------------|-------------|------------------------------------|--------------------------------------------------------------|----------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMIs | TRAVEL: Exposure - no modifiers | TRAVEL: efficiency (%) | Dilation ventilation effectiveness (%) | TRAC concentration factor | TRAC duration factor | TRAC factor | Extra exposure modifier (optional) | Free fact. comment to clarify additional modifier (optional) | Practical Exposure - points - modified |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Professional - SU22 | General exposures (closed systems) [CS15] | General exposures (closed systems) [CS107]; Process sampling [CS2]; | 0.01 | | | | | | | | 0.01 |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Professional - SU22 | General exposures (closed systems) [CS15] | Continuous process [CS54]; Process sampling [CS2] | 50.00 | | | | | | | | 50 |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Professional - SU22 | General exposures (closed systems) [CS15] | Batch process [CS55]; Process sampling [CS2] | 100.00 | | | | | | | | 100 |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Professional - SU22 | Process sampling [CS2]; (open systems) [CS106] | | 200.00 | | | | | | | | 250 |
| 5 | PROC 5 - Blending or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30] | Batch process [CS55]; Process sampling [CS2] with local exhaust ventilation [CS109] | 500.00 | 80.00 | | | | | | | 100 |
| 6 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30] | Batch process [CS55]; Process sampling [CS2] | 500.00 | | 50.00 | | | | | | 350 |
| 7 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30] | Batch process [CS55]; Process sampling [CS2] | 500.00 | | | | 1-4 hours | | | | 300 |
| 8 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banburys) [CS64]; with local exhaust ventilation [CS109] | | 600.00 | 80.00 | | | | | | | 400 |
| 9 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banburys) [CS64] | | 600.00 | | 30.00 | | | | | | 400 |
| 10 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banburys) [CS64] | | 600.00 | | | | 1-4 hours | | | | 300 |
| 11 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non-dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS2]; with local exhaust ventilation [CS109] | 500.00 | 80.00 | | | | | | | 100 |
| 12 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non-dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS2] | 500.00 | | 30.00 | | | | | | 300 |
| 13 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non-dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS2] | 500.00 | | | | 1-4 hours | | | | 300 |

22/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Professional Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-prof \ Inhalation Exposure

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | | Inhalation Exposure | | | | | | | |
|----------------------------|----------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|---------------------------------------|-----------------------|----------------------------------------|--------------------------|---------------------|----------------|------------------------------------|--------------------------------------------------------------|------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RHMIs | TRV predicted Exposure - no modifiers | TRVLEV efficiency (%) | Dilation ventilation effectiveness (%) | TRV concentration factor | TRV duration factor | TRV-RSE factor | Extra exposure modifier (optional) | Free fact. comment to clarify additional modifier (optional) | Produced Exposure - modifier |
| 14 | PROC 89 - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Dedicated facility [CS81] Transfer from/pouring from containers [CS2] | 250,00 | | | | | | | | 250 |
| 15 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Professional - SU22 | Small package filling [CS7] | Dedicated facility [CS81] Pouring from small containers [CS9] | 250,00 | | | | | | | | 250 |
| 16 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] ; with local exhaust ventilation [CS109] | 500,00 | 80,000 | | | | | | | 100 |
| 17 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] | 500,00 | | | 5-25 % | | | | | 300 |
| 18 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] | 500,00 | | | | 1-4 hours | | | | 300 |
| 19 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | with local exhaust ventilation [CS109] | 1000,00 | 80,00 | | | | | | | 200 |
| 20 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | 1000,00 | | 30,00 | | 1-4 hours | | | | 250 |
| 21 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | 1000,00 | | | | 15 min-1 hour | | | | 200 |
| 22 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | 1000,00 | | | | | half mask | | | 100 |
| 23 | PROC 13 - Treatment of articles by dipping and pouring | Professional - SU22 | Dipping, immersion and pouring [CS4] | | 250,00 | | | | | | | | 250 |
| 24 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion or extrusion, pelletator | Professional - SU22 | Production or preparation of articles by tableting, compression, extrusion or pelletation [CS100] | with local exhaust ventilation [CS109] | 500,00 | 80,00 | | | | | | | 100 |
| 25 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion, pelletator | Professional - SU22 | Production or preparation of articles by tableting, compression, extrusion or pelletation [CS100] | | 500,00 | | | | 1-4 hours | | | | 300 |
| 26 | PROC 15 - Use of laboratory reagents in small scale laboratories | Professional - SU22 | Laboratory activities [CS36] | | 50,00 | | | | | | | | 50 |

23/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Aceton-prof \ Inhalation Exposure Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | | | | | | | | | |
|-----------------------------------------------------------------------------|------------------------------------------------------------------|-----------------------------------------------------------------------------|------------------------------------------------------------|---------------------------------------|---------------------------------------|--------------------------|----------------------------------------|--------------------------|---------------------|----------------|------------------------------------|--------------------------------------------------------------|----------------------------------|
| Professional Processes relevant for Acetone and Acetone containing products | | Inhalation Exposure | | | | | | | | | | | |
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RHMs | ISA predicted Exposure - no modifiers | ISA LEV - efficiency (%) | Dilution ventilation effectiveness (%) | ISA concentration factor | ISA duration factor | ISA RPE factor | Extra exposure modifier (optional) | Free fact. comment to clarify additional modifier (optional) | Proposed Exposure - no modifiers |
| 27 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerpaints, pastels, adhesives [CS72] | | 500/50 | | | 5-25% | | | | | 300 |
| 28 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerpaints, pastels, adhesives [CS72] | | 500/50 | | | | 15 min-1 hour | | | | 100 |

24/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Aceton-prof \ Dermal Exposure Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | Dermal Exposure | | | | | | |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|-------------------------------------------|---------------------------|------------|------------------------------------|-------------------------------------------------------------|---------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario & typical RMMs | Operational Conditions & typical RMMs | TRIA Predicted Dermal exposure (mg/kg) - no modifiers | TRIA Dermal exposure LEV reduction factor | TRIA concentration factor | PPE factor | extra exposure modifier (optional) | Free text - comment to clarify additional modifier (dermal) | Weighted Dermal Exposure (mg/kg) - modified |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Professional - SU22 | General exposures (closed systems) [CS15]. | (closed systems) [CS107]; Process sampling [CS2]. ; | 0.34 | | | | | | 0.34 |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Professional - SU22 | General exposures (closed systems) [CS15]. | Continuous process [CS54]; Process sampling [CS2]. | 1.37 | | | | | | 1.37 |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Professional - SU22 | General exposures (closed systems) [CS15]. | Batch process [CS56]; Process sampling [CS2]. | 0.34 | | | | | | 0.34 |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure | Professional - SU22 | Process sampling [CS2]; (open systems) [CS109] | | 6.86 | | | | | | 6.86 |
| 5 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]. | Batch process [CS56]; Process sampling [CS2]; with local exhaust ventilation [CS109] | 13.71 | 0.01 | | | | | 0.07 |
| 6 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]. | Batch process [CS56]; Process sampling [CS2]. | 13.71 | | | | | | 13.71 |
| 7 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]. | Batch process [CS56]; Process sampling [CS2]. | 13.71 | | | | | | 13.71 |
| 8 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banbury) [CS64]; with local exhaust ventilation [CS109] | | 27.43 | 0.05 | | | | | 27.43 |
| 9 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banbury) [CS64] | | 27.43 | | | | | | 27.43 |
| 10 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banbury) [CS64] | | 27.43 | | | | | | 27.43 |
| 11 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non-dedicated facilities | Professional - SU22 | Bulk transfer [CS14]. | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]; with local exhaust ventilation | 13.71 | 0.01 | | | | | 0.14 |
| 12 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non-dedicated facilities | Professional - SU22 | Bulk transfer [CS14]. | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]. | 13.71 | | | | | | 13.71 |

25/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Acetone-prof \ Dermal Exposure Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | Dermal Exposure | | | | | | |
|----------------------------|-------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|-------------------------------------------------------|-------------------------------------------|---------------------------|------------|------------------------------------|-------------------------------------------------------------|---------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | TRIA Predicted Dermal exposure (mg/kg) - no modifiers | TRIA Dermal exposure LEV reduction factor | TRIA concentration factor | PPE factor | extra exposure modifier (optional) | Free text - comment to clarify additional modifier (dermal) | Weighted Dermal Exposure (mg/kg) - modified |
| 13 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22] | 13.71 | | | | | | 13.71 |
| 14 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Professional - SU22 | Bulk transfers [CS14] | Dedicated facility [CS81]; Transfer from/pouring from containers [CS22] | 6.86 | | | | | | 6.86 |
| 15 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Professional - SU22 | Small package filling [CS7] | Dedicated facility [CS81]; [CS9] | 6.86 | | | | | | 6.86 |
| 16 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39]; with local exhaust ventilation [CS109] | 27.43 | 0.050 | | | | | 1.37 |
| 17 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] | 27.43 | | 5-25% | | | | 16.46 |
| 18 | PROC 10 - Roller application or brushing | Professional - SU22 | Rolling, Brushing [CS51] | Or: Equipment cleaning and maintenance [CS39] | 27.43 | | | | | | 27.43 |
| 19 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | with local exhaust ventilation [CS109] | 107.14 | 0.02 | | | | | 2.14 |
| 20 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | 107.14 | | 5-25% | | | | 64.28 |
| 21 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | 107.14 | | | | | | 107.14 |
| 22 | PROC 11 - Non industrial spraying | Professional - SU22 | Spraying/fogging by manual application [CS24] | | 107.14 | | | | | | 107.14 |
| 23 | PROC 13 - Treatment of articles by dipping and pouring | Professional - SU22 | Dipping, immersion and pouring [CS4] | | 13.71 | | | | | | 13.71 |
| 24 | PROC 14 - Production of preparations or articles by labelling, compression, extrusion or extrusion, pelletisation | Professional - SU22 | Production or preparation of articles by labelling, compression, extrusion or pelletisation [CS103] | with local exhaust ventilation [CS109] | 3.43 | 0.10 | | | | | 0.34 |

26/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Professional Processes relevant for Acetone and Acetone containing products

CSR-Worker-Acetone-prof \ Dermal Exposure

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | | Dermal Exposure | | | | | | |
|----------------------------|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------|-------------------------------------------------------|-------------------------------------------|---------------------------|------------|-----------------------------------|-------------------------------------------------------------|---------------------------------------------|
| No | Use Descriptor (PROCs) | SU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | TRIA Predicted Dermal exposure (mg/kg) - no modifiers | TRIA Dermal exposure LEV reduction factor | TRIA concentration factor | PPE factor | extra exposure modifier (acetone) | Free text - comment to clarify additional modifier (dermal) | Weighted Dermal Exposure (mg/kg) - modified |
| 25 | PROC 14 - Production of preparations or articles by labelling, compression, extrusion, pelletisation | Professional - SU22 | Production or preparation of articles by labelling, compression, extrusion or pelletisation [CS100] | | 3.43 | | | | | | 3.43 |
| 26 | PROC 15 - Use of laboratory reagents in small scale laboratories | Professional - SU22 | Laboratory activities [CS36] | | 0.34 | | | | | | 0.34 |
| 27 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerpaints, pastels, adhesives [CS72] | | 141.43 | | 5-25% | gloves | | | 16.97 |
| 28 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerpaints, pastels, adhesives [CS72] | | 141.43 | | | | | | 141.43 |

27/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Acetone-prof \ RCR Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | Risk Characterization | | | |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|------------------|--------------|------------------|
| No | Use Descriptor (PROCs) | ISU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | RCR (Inhalation) | RCR (dermal) | RCR (all routes) |
| 1 | PROC 1 - Use in closed process, no likelihood of exposure | Professional - SU22 | General exposures (closed systems) [CS15]; | (closed systems) [CS107]; Process sampling [CS2]; ; | 0.00002 | 0.002 | 0.002 |
| 2 | PROC 2 - Use in closed, continuous process with occasional controlled exposure | Professional - SU22 | General exposures (closed systems) [CS15]; | Continuous process [CS54]; Process sampling [CS2]; | 0.10 | 0.01 | 0.11 |
| 3 | PROC 3 - Use in closed batch process (synthesis or formulation) | Professional - SU22 | General exposures (closed systems) [CS15]; | Batch process [CS55]; Process sampling [CS2]; | 0.20 | 0.002 | 0.20 |
| 4 | PROC 4 - Use in batch and other process (synthesis) where opportunity for exposure arises | Professional - SU22 | Process sampling [CS2]; (open systems) [CS106] | | 0.50 | 0.04 | 0.54 |
| 5 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]; | Batch process [CS55]; Process sampling [CS2]; with local exhaust ventilation [CS109] | 0.20 | 0.00 | 0.20 |
| 6 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]; | Batch process [CS55]; Process sampling [CS2]; | 0.70 | 0.07 | 0.77 |
| 7 | PROC 5 - Mixing or blending in batch processes (multistage and/or significant contact) | Professional - SU22 | Mixing operations (open systems) [CS30]; | Batch process [CS55]; Process sampling [CS2]; | 0.60 | 0.07 | 0.67 |
| 8 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banbury) [CS64]; with local exhaust ventilation [CS109] | | 0.84 | 0.15 | 0.99 |
| 9 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banbury) [CS64] | | 0.84 | 0.15 | 0.99 |
| 10 | PROC 6 - Calendaring operations | Professional - SU22 | Calendaring (including Banbury) [CS64] | | 0.72 | 0.15 | 0.87 |
| 11 | PROC 6a - Transfer of chemicals from to vessels/ large containers at non dedicated facilities | Professional - SU22 | Bulk transfers [CS14]; | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]; with local exhaust ventilation [CS109] | 0.20 | 0.001 | 0.20 |

28/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Acetone-prof \ RCR Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | Risk Characterization | | |
|----------------------------|-----------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-----------------------|--------------|------------------|
| No | Use Descriptor (PROCs) | Professional Products | Operational Conditions & typical RMMs | RCR (Inhalation) | RCR (dermal) | RCR (all routes) |
| 12 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Professional - SU22 Bulk transfers [CS14]. | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]. | 0.70 | 0.07 | 0.77 |
| 13 | PROC 8a - Transfer of chemicals from/to vessels/ large containers at non dedicated facilities | Professional - SU22 Bulk transfers [CS14]. | Non-dedicated facility [CS82]; Transfer from/pouring from containers [CS22]. | 0.60 | 0.07 | 0.67 |
| 14 | PROC 8b - Transfer of chemicals from/to vessels/ large containers at dedicated facilities | Professional - SU22 Bulk transfers [CS14]. | Dedicated facility [CS81]; Transfer from/pouring from containers [CS22]. | 0.50 | 0.04 | 0.54 |
| 15 | PROC 9 - Transfer of chemicals into small containers (dedicated filling line) | Professional - SU22 Small package filling [CS7]. | Dedicated facility [CS81]; Pouring from small containers [CS9]. | 0.50 | 0.04 | 0.54 |
| 16 | PROC 10 - Roller application or brushing | Professional - SU22 Rolling, Brushing [CS51]. | Or: Equipment cleaning and maintenance [CS39]. ; with local exhaust ventilation [CS109] | 0.20 | 0.007 | 0.21 |
| 17 | PROC 10 - Roller application or brushing | Professional - SU22 Rolling, Brushing [CS51]. | Or: Equipment cleaning and maintenance [CS39]. | 0.60 | 0.09 | 0.69 |
| 18 | PROC 10 - Roller application or brushing | Professional - SU22 Rolling, Brushing [CS51]. | Or: Equipment cleaning and maintenance [CS39]. | 0.60 | 0.15 | 0.75 |
| 19 | PROC 11 - Non industrial spraying | Professional - SU22 Spraying/fogging by manual application [CS24]. | with local exhaust ventilation [CS109] | 0.40 | 0.01 | 0.41 |
| 20 | PROC 11 - Non industrial spraying | Professional - SU22 Spraying/fogging by manual application [CS24]. | | 0.50 | 0.35 | 0.85 |
| 21 | PROC 11 - Non industrial spraying | Professional - SU22 Spraying/fogging by manual application [CS24]. | | 0.40 | 0.58 | 0.98 |
| 22 | PROC 11 - Non industrial spraying | Professional - SU22 Spraying/fogging by manual application [CS24]. | | 0.20 | 0.58 | 0.78 |

28/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

CSR-Worker-Acetone-prof \ RCR Professional Processes relevant for Acetone and Acetone containing products

| Generic Exposure Scenario: | | Professional Processes relevant for Acetone and Acetone containing products | | Risk Characterization | | | |
|----------------------------|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|----------------------------------------|------------------|--------------|------------------|
| No | Use Descriptor (PROCs) | ISU 3 / SU 22 | Contributing Scenario | Operational Conditions & typical RMMs | RCR (Inhalation) | RCR (dermal) | RCR (all routes) |
| 23 | PROC 13 - Treatment of articles by dipping and pouring | Professional - SU22 | Dipping, immersion and pouring [CS4]. | | 0.50 | 0.07 | 0.57 |
| 24 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation | Professional - SU22 | Production or preparation of articles by tableting, compression, extrusion or pelletisation [CS100] | with local exhaust ventilation [CS109] | 0.20 | 0.002 | 0.20 |
| 25 | PROC 14 - Production of preparations or articles by tableting, compression, extrusion, pelletisation | Professional - SU22 | Production or preparation of articles by tableting, compression, extrusion or pelletisation [CS100] | | 0.60 | 0.02 | 0.62 |
| 26 | PROC 15 - Use of laboratory reagents in small scale laboratories | Professional - SU22 | Laboratory activities [CS36]. | | 0.10 | 0.002 | 0.10 |
| 27 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerpaints, pastels, adhesives [CS72] | | 0.60 | 0.09 | 0.69 |
| 28 | PROC 19 - Hand-mixing with intimate contact (only PPE available) | Professional - SU22 | Hand application - fingerpaints, pastels, adhesives [CS72] | | 0.20 | 0.76 | 0.96 |

30/36

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

Acetone - Consumer

2010-08-23

Identified Consumer Generic Exposure Scenarios (GESs) of Acetone

| GES No. EC No. CAS No. | Subsector | Main SU | Description | PC |
|------------------------------|--------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| 1 | Uses in Coatings | All Consumer Uses (SU21) | Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including product transfer and preparation, application by brush, spray by hand or similar methods) and equipment cleaning. | PC1, PC4, PC5, PC9, PC10, PC15, PC24, PC31 |
| 2 | Use in Cleaning Agents | All Consumer Uses (SU21) | Covers general exposures to consumers arising from the use of household products sold as washing and cleaning products, aerosols, coatings, de-icers, lubricants and air care products. | PC3, PC4, PC9, PC24, PC32, PC 35, PC38 |
| 3 | De-icing and anti-icing applications | All Consumer Uses (SU21) | De-icing of vehicles and similar equipment by spraying | PC4 |

Identified Consumer - PCs & Market Sector - PCs

| PC | Acetone | | | PC type |
|------|----------|-----------|----------|---------------|
| | Coatings | Cleanings | De-icing | |
| PC1 | x | | | Consumer |
| PC3 | | x | | Consumer |
| PC4 | x | x | x | Market Sector |
| PC9 | x | x | | Consumer |
| PC15 | x | | | Market Sector |
| PC24 | x | x | | Consumer |
| PC31 | x | | | Consumer |
| PC32 | | x | | Market Sector |
| PC35 | | x | | Consumer |
| PC38 | | x | | Market Sector |

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main Sector of Use: All Consumer Uses

CSR-Consumer-Acetone

| Section 1 | Exposure Scenario Title |
|-----------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Title | GES USES |
| Sector of Use (SU code) | 21 |
| Use Descriptor (PC codes) | PC LISTS |
| Processes, tasks, activities covered | DESCRIPTIONS |
| Environmental Release Category | |
| Specific Environmental Release Category | |
| Section 2 | Operational conditions and risk management measures |
| <i>Field for additional statements to explain scenario if required - pending better understanding from ECHA</i> | |
| Section 2.1 | Control of consumer exposure |
| <i>Product characteristics</i> | |
| Physical form of product | liquid |
| Vapour pressure | 24000 |
| Concentration of substance in product | Unless otherwise stated, covers concentrations up to 100% [ConsOC1] |
| Amounts used | Unless otherwise stated, covers use amounts up to 37500g [ConsOC2]; covers skin contact area up to 6600cm ² [ConsOC5] |
| Frequency and duration of use/exposure | Unless otherwise stated, covers use frequency up to 4 times per day [ConsOC4]; covers exposure up to 8 hours per event [ConsOC14] |
| Other Operational Conditions affecting exposure | Unless otherwise stated assumes use at ambient temperatures [ConsOC15]; assumes use in a 20 m ³ room [ConsOC11]; assumes use with typical ventilation [ConsOC8]. |
| Section 2.1.1 | Product categories |
| PC1:Adhesives, sealants–Glues, hobby use | Unless otherwise stated, covers concentrations up to 30% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 35.73 cm ² [ConsOC5]; for each use event, covers use amounts up to 9g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14]; |
| PC1:Adhesives, sealants–Glues DIY-use (carpet glue, tile glue, wood parquet glue) | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 30% [ConsOC1]; covers use up to 1 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 110.00 cm ² [ConsOC5]; for each use event, covers use amounts up to 6390g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 6.00hr/event[ConsOC14]; |
| PC1:Adhesives, sealants–Glue from spray | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 30% [ConsOC1]; covers use up to 6 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 35.73 cm ² [ConsOC5]; for each use event, covers use amounts up to 85.05g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14]; |
| | No specific RMMs identified beyond those OCs stated |

32/36

Narr_High

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main Sector of Use: All Consumer Uses

CSR-Consumer-Acetone

| Section 2.1.1 | | Product categories |
|--------------------------------------------------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PC1:Adhesives, sealants--Sealants | OC | Unless otherwise stated, covers concentrations up to 30% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 35.73 cm2 [ConsOC5]; for each use event, covers use amounts up to 75g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 1.00hr/event[ConsOC14]; |
| PC3:Air care products--Air care, instant action (aerosol sprays) | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 4 times/day of use[ConsOC4]; for each use event, covers use amounts up to 0.1g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.25hr/event[ConsOC14]; |
| PC3:Air care products--Air care, continuous action (solid and liquid) | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 10% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 35.70 cm2 [ConsOC5]; for each use event, covers use amounts up to 0.48g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 8.00hr/event[ConsOC14]; |
| PC4_n:Anti-freeze and de-icing products--Washing car window | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 1% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 0.5g [ConsOC2]; Covers use in a one car garage (34m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.02hr/event[ConsOC14]; |
| PC4_n:Anti-freeze and de-icing products--Pouring into radiator | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 10% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 428.00 cm2 [ConsOC5]; for each use event, covers use amounts up to 2000g [ConsOC2]; Covers use in a one car garage (34m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.17hr/event[ConsOC14]; |
| PC4_n:Anti-freeze and de-icing products--Lock de-icer | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 214.40 cm2 [ConsOC5]; for each use event, covers use amounts up to 4g [ConsOC2]; Covers use in a one car garage (34m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.25hr/event[ConsOC14]; |
| PC9a:Coatings and paints, fillers putties, thinners--Waterborne latex wall paint | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 1.5% [ConsOC1]; covers use up to 4 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 428.75 cm2 [ConsOC5]; for each use event, covers use amounts up to 2760g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14]; |
| PC9a:Coatings and paints, fillers putties, thinners--Solvent rich, high solid, water borne paint | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 27.5% [ConsOC1]; covers use up to 6 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 428.75 cm2 [ConsOC5]; for each use event, covers use amounts up to 744g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14]; |
| | RMM | No specific RMMs identified beyond those OCs stated |

33/36

Narr_High

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main Sector of Use: All Consumer Uses

CSR-Consumer-Acetone

| Section 2.1.1 | | Product categories |
|---------------------------------------------------------------------------------------------------------------|-----|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PC9a: Coatings and paints, fillers putties, thinners-- Aerosol spray can | RMM | Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 2 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 215g [ConsOC2]; Covers use in a one car garage (34m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| PC9a: Coatings and paints, fillers putties, thinners-- Removers (paint-, glue-, wall paper-, sealant-remover) | OC | Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 3 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 857.50 cm2 [ConsOC5]; for each use event, covers use amounts up to 491g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.00hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| PC9b: Fillers, putties, plasters, modelling clay-- Fillers and putty | RMM | No specific RMMs identified beyond those OCs stated |
| PC9b: Fillers, putties, plasters, modelling clay-- Fillers and putty | OC | Unless otherwise stated, covers concentrations up to 2% [ConsOC1]; covers use up to 12 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 35.73 cm2 [ConsOC5]; for each use event, covers use amounts up to 85g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 4.00hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| PC9b: Fillers, putties, plasters, modelling clay-- Plasters and floor equalizers | RMM | No specific RMMs identified beyond those OCs stated |
| PC9b: Fillers, putties, plasters, modelling clay-- Modelling clay | OC | Unless otherwise stated, covers concentrations up to 2% [ConsOC1]; covers use up to 12 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 857.50 cm2 [ConsOC5]; for each use event, covers use amounts up to 13800g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.00hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| PC9c: Finger paints --Finger paints | RMM | No specific RMMs identified beyond those OCs stated |
| PC9c: Finger paints --Finger paints | OC | Unless otherwise stated, covers concentrations up to 1% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 254.40 cm2 [ConsOC5]; for each use event, assumes swallowed amount of 1g [ConsOC13]; No specific RMMs identified beyond those OCs stated |
| PC15_n: Non-metal surface treatment products-- Solvent rich, high solid, water borne paint | RMM | Avoid using at a product concentration greater than 5% [ConsRMM1]; Unless otherwise stated, covers concentrations up to 27.5% [ConsOC1]; covers use up to 6 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 428.75 cm2 [ConsOC5]; for each use event, covers use amounts up to 744g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.20hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| PC15_n: Non-metal surface treatment products-- Aerosol spray can | RMM | No specific RMMs identified beyond those OCs stated |
| PC15_n: Non-metal surface treatment products-- Aerosol spray can | OC | Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 2 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 215g [ConsOC2]; Covers use in a one car garage (34m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| PC15_n: Non-metal surface treatment products-- Removers (paint-, glue-, wall paper-, sealant-remover) | RMM | No specific RMMs identified beyond those OCs stated |
| PC15_n: Non-metal surface treatment products-- Removers (paint-, glue-, wall paper-, sealant-remover) | OC | Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 3 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 857.50 cm2 [ConsOC5]; for each use event, covers use amounts up to 491g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 2.00hr/event[ConsOC14]; No specific RMMs identified beyond those OCs stated |
| | RMM | No specific RMMs identified beyond those OCs stated |

34/36

Narr_High

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main Sector of Use: All Consumer Uses

CSR-Consumer-Acetone

| Section 2.1.1 | | Product categories |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PC24: Lubricants, greases, and release products--OC Liquids | OC | Unless otherwise stated, covers concentrations up to 100% [ConsOC1]; covers use up to 4 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 488.00 cm2 [ConsOC5]; for each use event, covers use amounts up to 2200g [ConsOC2]; Covers use in a one car garage (34m3) under typical ventilation [ConsOC10]; covers use in room size of 34m3[ConsOC11]; for each use event, covers exposure up to 0.17hr/event[ConsOC14]; |
| PC24: Lubricants, greases, and release products--OC Pastes | RMM OC | Unless otherwise stated, covers concentrations up to 20% [ConsOC1]; covers use up to 10 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 488.00 cm2 [ConsOC5]; for each use event, covers use amounts up to 34g [ConsOC2]; covers use in room size of m3[ConsOC11]; |
| PC24: Lubricants, greases, and release products--OC Sprays | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 6 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 428.75 cm2 [ConsOC5]; for each use event, covers use amounts up to 73g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.17hr/event[ConsOC14]; |
| PC31: Polishes and wax blends--Polishes, wax / cream (floor, furniture, shoes) | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 29 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 430.00 cm2 [ConsOC5]; for each use event, covers use amounts up to 142g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 1.23hr/event[ConsOC14]; |
| PC31: Polishes and wax blends--Polishes, spray (furniture, shoes) | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 50% [ConsOC1]; covers use up to 8 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 430.00 cm2 [ConsOC5]; for each use event, covers use amounts up to 35g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14]; |
| PC35: Washing and cleaning products (including solvent based products)--Laundry and dish washing products | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 5% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 857.50 cm2 [ConsOC5]; for each use event, covers use amounts up to 15g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.50hr/event[ConsOC14]; |
| PC35: Washing and cleaning products (including solvent based products)--Cleaners, liquids (all purpose cleaners, sanitary products, floor cleaners, glass cleaners, carpet cleaners, metal cleaners) | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 5% [ConsOC1]; covers use up to 128 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 857.50 cm2 [ConsOC5]; for each use event, covers use amounts up to 27g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.33hr/event[ConsOC14]; |
| PC35: Washing and cleaning products (including solvent based products)--Cleaners, trigger sprays (all purpose cleaners, sanitary products, glass cleaners) | RMM OC | No specific RMMs identified beyond those OCs stated Unless otherwise stated, covers concentrations up to 15% [ConsOC1]; covers use up to 128 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; covers skin contact area up to 428.00 cm2 [ConsOC5]; for each use event, covers use amounts up to 35g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m3[ConsOC11]; for each use event, covers exposure up to 0.17hr/event[ConsOC14]; |
| | RMM | No specific RMMs identified beyond those OCs stated |

35/36

Narr_High

Aceton

Version 8.0

Date de révision 07.12.2010

Date d'impression 17.12.2010

2010-08-23

Main Sector of Use: All Consumer Uses

CSR-Consumer-Acetone

| | |
|--------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Section 2.1.1 | Product categories |
| PC38 n: Welding and soldering products, flux products--NOTE: n_assessment not in TRA | Unless otherwise stated, covers concentrations up to 20% [ConsOC1]; covers use up to 365 days/year[ConsOC3]; covers use up to 1 time/on day of use[ConsOC4]; for each use event, covers use amounts up to 12g [ConsOC2]; covers use under typical household ventilation [ConsOC8]; covers use in room size of 20m ³ [ConsOC11]; for each use event, covers exposure up to 1.00hr/event[ConsOC14]; |
| Section 3 | Exposure Estimation ('Flexible' heading) |
| | No specific RMMs identified beyond those OCs stated |
| Section 3 | Exposure Estimation ('Flexible' heading) |
| | ECHA Note in draft template: Exposure estimation and risk characterisation ratios (for all routes of exposure for consumers and all compartments for environment) resulting from the conditions described under Sections 2.1 and 2.2), and the substance properties; make reference to the exposure assessment tool applied. Note: Detail could be confusing for customers. Also may be an extensive list. Proposal to include a weblink from where these data can be retrieved (a component of GES development). |
| 3.1. Health | |
| Health sub-headings (design as phrases) | Standard phrases expected. Ability to include a web link. |
| 3.2. Environment | |
| Environment sub-headings (design as phrases) | Standard phrases expected. Ability to include a web link. |
| Section 4 | |
| | Guidance to check compliance with the Exposure Scenario ('Flexible' heading) |
| | Guidance how the DU can evaluate whether he operates within the conditions set in the exposure scenario - scaling tools. Standard phrases |
| 4.1. Health | |
| Health sub-headings (design as phrases) | Utilize TRA, TRA+ and/or CONSEXPO exposure model |
| 4.2. Environment | |
| Environment sub-headings (design as phrases) | Standard phrases |

36/36

Narr_High